

---

# AQUA PROTECTION

---



www.vieropaints.com  
info@vieropaints.it

Product data sheet: VID455173T  
Rev. 01 dated 31/07/2018

<b>Name</b>	<b>AQUA PROTECTION</b>
<b>Description</b>	Protective water-repellent and transparent water-based finish. Also perfect for lime-based primers.
<b>Product characteristics</b>	AQUA PROTECTION is a transparent, water-repellent and extremely matt protective finish with exceptionally high protective ability, and is suitable for both mineral and acrylic finishes. AQUA PROTECTION has been specially formulated to leave the natural surface of lime putty-based products intact, allowing for regular cleaning even with aggressive detergents. It is UV resistant and non-yellowing.
<b>Produced in</b>	MADE IN ITALY
<b>Main application tools</b>	Roller, brush
<b>Achievable effects</b> <b>Application method</b>	<p>AQUA PROTECTION should be applied only after the surface is complete dry, as indicated in the relative technical data sheets. AQUA PROTECTION may not be applied to surfaces coated with mineral base products until 48 hours after base application. FOR SURFACES IN CONTINUOUS CONTACT WITH WATER (e.g. Shower Box) OR EXTERIORS: (please see Application guide on the preparation of the base)</p> <p>Shake product thoroughly before application.</p> <p>Apply AQUA PROTECTION onto clean and dry surfaces, after diluting properly according to the instructions below, waiting 24 hours between coats:</p> <p>Use a brush to apply the first coat, diluted 100% with water;</p> <p>Use a short-haired roller to apply the second coat, diluted 50% with water;</p> <p>Use a short-haired roller to apply the third coat, diluted no more than 20% with water;</p> <p>Mineral/Acrylic Finishes:</p> <p>After drying, clean the surface thoroughly and apply AQUA PROTECTION using the methods described below, waiting 24 hours between coats:</p> <p>Use a brush to apply the first coat, diluted 100% with water;</p> <p>Use a short-haired roller to apply the second coat, diluted 50% with water;</p>
<b>Practical tips</b>	<p>Do not apply the product on surfaces exposed to direct sunlight or in the presence of strong drafts. The base coat should be set, clean and free from any chipping, peeling and/or dampness. New plasters should be left to age for at least 4-5 weeks to allow for complete carbonation.</p> <p>Environmental conditions -&gt; temperature: min. + 5 °C/max. + 35 °C, relative humidity: &lt; 75%.</p> <p>Primer conditions -&gt; temperature: min. + 5 °C/max. + 35 °C, humidity: &lt; 10 with respect to relative humidity.</p> <p>Shake the product before use or, if it is very dense, use a spatula or a mixing drill to achieve a workable consistency.</p> <p>After applications, surfaces should be protected against water, driving rain, freezing temperatures (temp &gt; 5 °C), fog, dew, and dust for at least 5 days.</p> <p>The product's water-repellent properties are fully achieved after 7 days. The product may not be stored for more than 48 hours after dilution.</p> <p>Rinse used tools with water immediately after use.</p> <p>Keep the paint can sealed and away from freezing temperatures and sunlight.</p>
<b>Safety precautions</b>	<p>Safety information for users is contained in the relative safety data sheet.</p> <p>Empty containers or containers with traces of dried product film should be disposed of according to local regulations.</p>

## FOR PROFESSIONAL USE ONLY

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

Viero is a trademark of Cromology Italia S.p.A. - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424

# AQUA PROTECTION

# Viero

www.vieropaints.com  
info@vieropaints.it

Product data sheet: VID455173T  
Rev. 01 dated 31/07/2018

TECHNICAL/REGULATORY INFORMATION	APPLICABLE REGULATION	INFO AT 20 °C AND 60% HUMIDITY
Appearance in the can Finish appearance		Liquid Transparent
Density g/ml	UNI 8910	1,02 ÷ 1,10
Natural spread rate (lt/m <sup>2</sup> )	ISO 7254	0.2 - 0.25
Flash point °C	UNI 8909	Non-flammable
Shelf life (in a cool and dry place)	UNI 10154.	At least 12 months
Hard dry Hours (h)		48
Application places		Interiors/Exteriors
Bases + achievable colours		Transparent
Binder		Acrylic
Tool cleaning		Water
Dilution % by volume		1 brush coat with 100% water 2 short-haired roller coat with 50% water 3 short-haired roller coat with no more than 20% water

## FOR PROFESSIONAL USE ONLY

Toll Free Number: 800.219.420 (Italy)  
International assistance: +39.0583.2424 (from other countries)

Mon - Fri [8:00 am/1:00 pm - 2:00 pm/5:30 pm]



**CROMOLOGY**  
Italia

COMPANY WITH  
MANAGEMENT SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =  
= ISO 14001 =  
= OHSAS 18001 =

The information provided is based on our best technical and practical knowledge, but all advice and suggestions are given without any guarantee since the conditions of use are not under our direct control. In case of doubt, it is always advisable to carry out preliminary tests and/or to call our technicians.

**Viero is a trademark of Cromology Italia S.p.A.** - Via IV Novembre, 4 - 50016 Porcari (LU) VAT no.: 07684621001 - ITALY - Ph.: +39 0584 2424